

Liquefied Petroleum Gas

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reference number: AWO006 Issue date: 12/31/2021 Revision date: 12/31/2021 Supersedes version of: 8/26/2019 Version: 2.4

Danger



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

SDS no

: AWO006

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

 Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory use.
 Contact supplier for more information on uses.

1.3. Details of the supplier of the safety data sheet

Woikoski Oy PL1 52020 Woikoski – Finland Finland T +358 40 166 2023 asiakaspalvelu@woikoski.fi - www.woikoski.fi

1.4. Emergency telephone number

No additional information available

SECTION 2: Hazards identification

Classification according	g to Regulation (EC) No. 127	72/2008 [CLP]
Physical hazards	Flammable gases, Catego	ry 1A H220
	Gases under pressure : Co	ompressed gas H280
2.2. Label elements		
Labelling according to	Regulation (EC) No. 1272/20	08 [CLP]
Hazard pictograms (CLP)		GHS02 GHS04
Signal word (CLP)	:	Danger
Hazard statements (CLP)	:	H220 - Extremely flammable gas.
		H280 - Contains gas under pressure; may explode if heated.
Precautionary statements	s (CLP)	
- Prevention	:	P210 - Keep away from heat, hot surfaces, open flames, sparks No smoking.
- Response	:	P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
		P381 - Eliminate all ignition sources if safe to do so.
- Storage		P403 - Store in a well-ventilated place.



Liquefied Petroleum Gas

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reference number: AWO006

2.3. Other hazards

None.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propane	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944-21	> 95	Flam. Gas 1A, H220 Press. Gas (Liq.), H280
butane	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691-32	< 5	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

SECTION 4: First aid measures			
4.1. Description of first aid mea	asures		
- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.		
- Skin contact	: Adverse effects not expected from this product.		
- Eye contact	: Adverse effects not expected from this product.		
- Ingestion	: Ingestion is not considered a potential route of exposure.		
4.2. Most important symptoms and effects, both acute and delayed			
	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.		

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
 Suitable extinguishing media Unsuitable extinguishing media 	Water spray or fog.Carbon dioxide.Do not use water jet to extinguish.	
5.2. Special hazards arising from the substance or mixture		
Specific hazards Hazardous combustion products	Exposure to fire may cause containers to rupture/explode.Carbon monoxide.	



Liquefied Petroleum Gas

face mask.

. according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reference number: AWO006

5.3. Advice for firefighters	
Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
Special protective equipment for fire fighters	 In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Try to stop release. Evacuate area. Consider the risk of potentially explosive atmospheres. Eliminate ignition sources. Ensure adequate air ventilation.
	Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
6.2. Environmental precautions	
	Try to stop release.
6.3. Methods and material for containment	nt and cleaning up
	Ventilate area.
6.4. Reference to other sections	
	See also sections 8 and 13.
SECTION 7: Handling and storag	e
7.1. Precautions for safe handling	
Safe use of the product	 The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment. Purge air from system before introducing gas. Take precautionary measures against static discharge. Keep away from ignition sources (including static discharges). Consider the use of only non-sparking tools.



Liquefied Petroleum Gas

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reference number: AWO006

Safe handling of the gas receptacle	 Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container.
7.2. Conditions for safe storage, including	 any incompatibilities Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials. Segregate from oxidant gases and other oxidants in store. All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.
7.3. Specific end use(s)	None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Keep concentrations well below lower explosion limits. Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities. 8.2.2. Individual protection measures, e.g. personal protective equipment A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. · Eye/face protection Wear safety glasses with side shields. : Standard EN 166 - Personal eye-protection - specifications. Skin protection

WOIKOSKI

Safety Data Sheet

Liquefied Petroleum Gas

. according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reference number: AWO006

- Hand protection	: Wear working gloves when handling gas containers.
	Standard EN 388 - Protective gloves against mechanical risk.
- Other	: Consider the use of flame resistant anti-static safety clothing.
	Standard EN ISO 14116 - Limited flame spread materials.
	Standard EN 1149-5 - Protective clothing: Electrostatic properties.
	Wear safety shoes while handling containers.
	Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	: Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
	Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.
Thermal hazards	: None necessary.
8.2.3. Environmental exposure controls	
	Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for

specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
 Physical state at 20°C / 101.3kPa 	: Gas
- Colour	: Mixture contains one or more component(s) which have the following colour(s):
	Colourless.
Odour	: There may be no odour warning properties, odour is subjective and inadequate to warn of
	overexposure.
	Mixture contains one or more component(s) which have the following odour:
	Stenchant often added. Sweetish.
	Odour threshold is subjective and inadequate to warn of overexposure.
	Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gas mixtures.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
Flash point	: Not applicable for gas mixtures.
Flammability	: Flammability range not available.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not available
Density	: Not applicable
Vapour density	: Not available
Relative density, liquid (water=1)	: Not applicable
Relative density, gas (air=1)	: Heavier than air.
Water solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
Viscosity, kinematic	: Not applicable.
Particle characteristics	: Not applicable
9.2. Other information	

9.2. Other information

9.2.1. Information with regard to physical hazard classes			
Explosive properties	: Not applicable.		
Oxidising properties	: None.		
9.2.2. Other safety characteristics			

Molar mass	:	Not applicable for gas mixtures.
Evaporation rate	:	Not applicable for gas mixtures.



Liquefied Petroleum Gas

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reference number: AWO006

Other data

: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity		
10.1. Reactivity		
	No reactivity hazard other than the effects described in sub-sections below.	
10.2. Chemical stability		
	Stable under normal conditions.	
10.3. Possibility of hazardous reactions		
	Can form explosive mixture with air. May react violently with oxidants.	
Reactivity	: This mixture contains components with the following reactivity : Can form explosive mixture with air. May react violently with oxidants.	
10.4. Conditions to avoid		
	Keep away from heat/sparks/open flames/hot surfaces. – No smoking.	
10.5. Incompatible materials		
	No additional information available	
10.6. Hazardous decomposition products		
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.	

SECTION 11: Toxicological information		
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008		
Acute toxicity	: No toxicological effects from this product.	
propane (74-98-6)		
LC50 Inhalation - Rat [ppm]	20000 ppm/4h	
Skin corrosion/irritation	: No known effects from this product.	
Serious eye damage/irritation	: No known effects from this product.	
Respiratory or skin sensitisation	: No known effects from this product.	
Germ cell mutagenicity	: No known effects from this product.	
Carcinogenicity	: No known effects from this product.	
	. No known official from this product	

Toxic for reproduction : Fertility: No known effects from this product.Toxic for reproduction : unborn child: No known effects from this product.STOT-single exposure: No known effects from this product.STOT-repeated exposure: No known effects from this product.Aspiration hazard: Not applicable for gases and gas mixtures.

11.2. Information on other hazards

No additional information available

EC50 72h Algae

SECTION 12: Ecological information		
<u>12.1. Toxicity</u>		
Assessment	: Classification criteria are not met.	
EC50 48h - Daphnia magna	: No data available.	

: No data available.



Liquefied Petroleum Gas

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reference number: AWO006

LC50-96 h - fish :	No data available.
butane (106-97-8)	
EC50 48h - Daphnia magna	14.2 mg/l
EC50 72h Algae	7.7 mg/l
LC50-96 h - fish	24.1 mg/l
propane (74-98-6)	
EC50 48h - Daphnia magna	27.1 mg/l
EC50 72h Algae	11.9 mg/l
LC50-96 h - fish	49.9 mg/l
12.2. Persistence and degradability	
Assessment :	No data available.
12.3. Bioaccumulative potential	
Assessment :	No data available.
<u>12.4. Mobility in soil</u>	
Assessment :	No data available.
12.5. Results of PBT and vPvB assessment	
Assessment :	No data available.
12.6. Endocrine disrupting properties	
No additional information available	
12.7. Other adverse effects	
	None. Contains greenhouse gas(es).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	 Contact supplier if guidance is required. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.eu for more guidance on suitable disposal methods. 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.
13.2. Additional information	

None.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN		
UN-No.	:	196



Liquefied Petroleum Gas

. according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reference number: AWO006

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

- : HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S. (propane, butane)
- : Hydrocarbon gas mixture, liquefied, n.o.s. (propane, butane)
 - : HYDROCARBON GAS MIXTURE, LIQUEFIED, N.O.S. (propane, butane)

14.3. Transport hazard class(es)

Labelling

Labelling	
	2.1 : Flammable gases.
Transport by road/rail (ADR/RID)	
Class	: 2
Classification code	: 2F
Hazard identification number	: 23
Tunnel Restriction	: B/D - Tank carriage : Passage forbidden through tunnels of category B, C, D and E. Other carriage : Passage forbidden through tunnels of category D and E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.1
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.1
Emergency Schedule (EmS) - Fire Emergency Schedule (EmS) - Spillage	: F-D : S-U
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.
14.6. Special precautions for user	
Packing Instruction(s)	
Transport by road/rail (ADR/RID)	: P200
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: Forbidden.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment.
	Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in
	the event of an accident or an emergency.
	Before transporting product containers:
	- Ensure there is adequate ventilation.
	- Ensure that containers are firmly secured.
	- Ensure valve is closed and not leaking.
	- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
	- Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.



Liquefied Petroleum Gas

. according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Reference number: AWO006

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations	
Restrictions on use Other information, restriction and prohibition regulations Seveso Directive : 2012/18/EU (Seveso III)	 Contains no substance on the REACH candidate list Ensure all national/local regulations are observed. Covered.
National regulations	
No additional information available	
15.2. Chemical safety assessment	
	A CSA does not need to be carried out for this product.

SECTION 16: Other information	
Indication of changes	: Safety data sheet in accordance with commission regulation (EU) No 2020/878.
Training advice	: Ensure operators understand the flammability hazard. Receptacle under pressure.
Further information	 This Safety Data Sheet has been established in accordance with the applicable European Union legislation. Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).

Full text of H- and EUH-statements	
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

DISCLAIMER OF LIABILITY

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the proparation of this document, no liability for injult

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document